

REQUEST FOR BIDS

The City of Batesville is accepting sealed bids for a new Dump Truck. Bid sheet, notification and specification packets can be provided by calling 870-698-2400 ext. 108 or on the City's web site at www.batesvillearkansas.gov Bids will be opened August 13, 2025 at 10:30 am at the Batesville Municipal Building, 500 E. Main Street, Batesville, AR 72501

The City reserves the right to reject any or all bids.

NOTICE TO BIDDERS

Notice is hereby given that the City of Batesville of Independence County, AR will receive written sealed bids until _____ A.M. on _____, 20__, for the purchase and/or lease purchase of three (3) or more new 2026 Model Year Tandem Axle Dump Trucks.

Instructions to Bidders:

1. No responsibility will be attached to any person employed by the City of Batesville of Independence County, AR, for the premature opening of any bid not properly addressed and identified as stipulated below:
BID FOR: New Dump Truck
OPENING DATE / TIME: _____
2. All equipment / trucks offered in the bid must be new and in unused condition. Only 2026 year or newer models will be considered
3. Any exceptions to the specifications must be listed in the Bidders bid with justification. Failure to do so will disqualify the bid.
4. Price bid shall be for F.O.B. Independence County, AR, and must include any pre-delivery and/or setup charges, title fees and inspection fees.
5. The Bidder shall complete the unit price bid with no further calculations required in order to determine the firm unit price.
6. Bid must be signed and dated by the Bidders Authorized Agent.
7. All bids must state Manufacturer Warranty.
8. All bids must state approximate delivery time.
9. Locations for parts and service must be included in the bid and will be a factor in determining the best bid.
10. All Bidders must secure a bid sheet along with specifications. Bid sheet must be completed in entirety before submission as a formal bid.

11. All Bidders must offer a **guaranteed** residual at the end of the term specified on "Bidders Sheet". All terms, conditions, and/or limitations specific to the equipment at time of turn in must be clearly stated.
12. It shall be incumbent upon each Bidder to understand the specifications on the bid form and to obtain clarification when necessary. It is not the intent of the specifications to limit the bidding process to any make or manufacturer, but to fill a specific need and to perform a specific task.
13. The City of Batesville of Independence County, AR reserves the right to determine which is the lowest and best bid and to accept or reject any or all bids based on that determination.
14. Questions per the above should be directed to:

djustice@batesvillearkansas.gov

Bid Sheet

Sales Price: _____

Payment Amount: _____

Guaranteed Residual: _____

Term: _____

Interest Rate: _____

Lessor Name: _____

Lessor Address: _____

Lessor City/State/Zip: _____

Contact: _____

Contact Phone Number: _____

Primary Email Address: _____

Lease Expenses:

Please Provide the Following Information:

Indicative Interest Rate: _____

Please state **ALL** Terms & Conditions applicable to the financial package proposed.

NOTE: Bidder must quote simple interest only with no pre-payment penalty for Early Payoff.

Authorized Signature

Date

Bid Specifications
Conventional Chassis for Tandem Axle Dump Truck

Complete by Checking the Following
IF NOT COMPLIANT, **state Specifically** the item being offered

	<u>YES</u>	<u>NO</u>	<u>OFFERED</u>
Model Year 2026	<input type="checkbox"/>	<input type="checkbox"/>	_____
 <u>Wheelbase/Frame</u>			
Wheelbase 226"	<input type="checkbox"/>	<input type="checkbox"/>	_____
CA 139"	<input type="checkbox"/>	<input type="checkbox"/>	_____
Platform 195"	<input type="checkbox"/>	<input type="checkbox"/>	_____
AF 57"	<input type="checkbox"/>	<input type="checkbox"/>	_____
BBC – Minimum 116" With Flush Mount Bumper	<input type="checkbox"/>	<input type="checkbox"/>	_____
Frame – 11.811" X 4.13" X .44 Steel	<input type="checkbox"/>	<input type="checkbox"/>	_____
with 3,160,000 in lbs. per rail			
Extended Bright Finish Steel Bumper with Center Tow	<input type="checkbox"/>	<input type="checkbox"/>	_____
Pin And Stone Guard			
HD Crossmembers	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rear Tow Hooks	<input type="checkbox"/>	<input type="checkbox"/>	_____
 <u>Engine</u>			
Electronically controlled 4-cycle diesel, in line 6 cyl., Turbocharged with air-to-air inter-cooler, minimum 659 cubic inch sleeved engine, minimum of 425 HP with 1560 ft/lbs. torque, all spin-on filters (fuel, oil, water).	<input type="checkbox"/>	<input type="checkbox"/>	_____
NOTE: Bids will be accepted only with engines certified by the EPA to meet 2017 EPA Regulations			

Air Compressor – 18.7 CFM	<input type="checkbox"/>	<input type="checkbox"/>	_____
Alternator – 12V 135A	<input type="checkbox"/>	<input type="checkbox"/>	_____
Batteries – Group 31 650/1950 Threaded Stud Type	<input type="checkbox"/>	<input type="checkbox"/>	_____
Bug Screen	<input type="checkbox"/>	<input type="checkbox"/>	_____
Texaco Long Life Engine Coolant to -34 Deg F	<input type="checkbox"/>	<input type="checkbox"/>	_____
Engine Brake	<input type="checkbox"/>	<input type="checkbox"/>	_____
Engine Block Heater	<input type="checkbox"/>	<input type="checkbox"/>	_____
Electronic Variable Fan Clutch	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fuel-Water Separator	<input type="checkbox"/>	<input type="checkbox"/>	_____
Starter – 12-Volt	<input type="checkbox"/>	<input type="checkbox"/>	_____
Exhaust – Single Bright Finish Vertical Cab Mtd Exhaust	<input type="checkbox"/>	<input type="checkbox"/>	_____
Diesel Particulate Filter Frame Mounted RH	<input type="checkbox"/>	<input type="checkbox"/>	_____
Side Under Cab			
D.P.F. Serviceable Without Special Tools	<input type="checkbox"/>	<input type="checkbox"/>	_____
DPF cover stainless Steel, Polished	<input type="checkbox"/>	<input type="checkbox"/>	_____
Single, Bright finish Heat shield, Stack and SCR cover (if equipped)	<input type="checkbox"/>	<input type="checkbox"/>	_____
Battery box cover- Polished aluminum	<input type="checkbox"/>	<input type="checkbox"/>	_____

Transmission/Clutch/Drive Lines

Automated Heavy Duty 12 SP –(overdrive) 12 Forward Gears

With hill start assist	<input type="checkbox"/>	<input type="checkbox"/>	_____
Transmission Oil Cooler	<input type="checkbox"/>	<input type="checkbox"/>	_____
Synthetic Fluid	<input type="checkbox"/>	<input type="checkbox"/>	_____
Driveline Main Spicer SPL 250HDXL		<input type="checkbox"/>	<input type="checkbox"/> _____
Driveline – Interaxle Spicer SPL 250XL	<input type="checkbox"/>	<input type="checkbox"/>	_____
PTO- factory mounted	<input type="checkbox"/>	<input type="checkbox"/>	_____
<u>Front Axle</u>			
Front Axle – 18,000 lb	<input type="checkbox"/>	<input type="checkbox"/>	_____
Springs – Taper-leaf 18,000 lb. Ground Rating	<input type="checkbox"/>	<input type="checkbox"/>	_____
Front Shock Absorbers	<input type="checkbox"/>	<input type="checkbox"/>	_____
Integral Power Steering	<input type="checkbox"/>	<input type="checkbox"/>	_____
Slack Adjusters Automatic	<input type="checkbox"/>	<input type="checkbox"/>	_____
Brakes – Meritor S Cam 16.5” x 6” Q+	<input type="checkbox"/>	<input type="checkbox"/>	_____
Wheels – Polished Aluminum Disc 22.5 X 12.25	<input type="checkbox"/>	<input type="checkbox"/>	_____
Hub Piloted			
Tires – Michelin XZE 425/65R22.5	<input type="checkbox"/>	<input type="checkbox"/>	_____
Tapered King Pins with no Adjustment Required	<input type="checkbox"/>	<input type="checkbox"/>	_____
Unitized wheel hubs with permanent wheel seals	<input type="checkbox"/>	<input type="checkbox"/>	_____
Dust Shields	<input type="checkbox"/>	<input type="checkbox"/>	_____

Rear Axle

Rear Axle – 44,000 lb. double reduction with 44,000 lb. Anti- sway springs	<input type="checkbox"/>	<input type="checkbox"/>	_____
Power Divider Lockout	<input type="checkbox"/>	<input type="checkbox"/>	_____
Bronze Trunnion Bushings	<input type="checkbox"/>	<input type="checkbox"/>	_____
Slack Adjusters Automatic	<input type="checkbox"/>	<input type="checkbox"/>	_____
Brakes – Meritor S Cam 16.5” x 7” Q+	<input type="checkbox"/>	<input type="checkbox"/>	_____
Dust Shields	<input type="checkbox"/>	<input type="checkbox"/>	_____
Wheels – Alcoa ultra one alum 24.5 X 8.25 Hub Piloted	<input type="checkbox"/>	<input type="checkbox"/>	_____
Tires – Bridgestone M799 11r 24.5	<input type="checkbox"/>	<input type="checkbox"/>	_____
Synthetic Lubricant	<input type="checkbox"/>	<input type="checkbox"/>	_____

NOTE: Bids will only be accepted on the following Rear Axles:

Mack S440 or Dana-Spicer DP463-P

Cab (Interior Features)

AM/FM Radio with CD, MP3, Weatherband, Handsfree Interface, and Bluetooth	<input type="checkbox"/>	<input type="checkbox"/>	_____
Coat Hooks	<input type="checkbox"/>	<input type="checkbox"/>	_____
Dispatch Box Mounted on Rear Panel	<input type="checkbox"/>	<input type="checkbox"/>	_____
Overhead Console including 2 Storage Compartments With Retaining Nets	<input type="checkbox"/>	<input type="checkbox"/>	_____
Heater with Integral Defroster	<input type="checkbox"/>	<input type="checkbox"/>	_____

Air Conditioner Factory Installed	<input type="checkbox"/>	<input type="checkbox"/>	_____
Dome Lights – 2 Driver’s side, 2 Passenger Side	<input type="checkbox"/>	<input type="checkbox"/>	_____
Steering Wheel, 2 Spoke Uretane Grip w/ switches for radio and cruise control	<input type="checkbox"/>	<input type="checkbox"/>	_____
Infinitely Adjusting Steering Column, Tilt and Telescope	<input type="checkbox"/>	<input type="checkbox"/>	_____
Seats:			
Driver – Air Susp. (Hi-Back) 4 chamber air Lumbar, bolster, extension	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rider – Non-Suspension	<input type="checkbox"/>	<input type="checkbox"/>	_____
Seat Belts – Driver and Rider Lap & Shoulder With Cab Mounted Shoulder Belt	<input type="checkbox"/>	<input type="checkbox"/>	_____
Sun Visors Interior– LH and RH	<input type="checkbox"/>	<input type="checkbox"/>	_____
T.M.C. Recommended Instrument Panel	<input type="checkbox"/>	<input type="checkbox"/>	_____
Driver Information Display	<input type="checkbox"/>	<input type="checkbox"/>	_____
Air Pressure Gauge – Dual	<input type="checkbox"/>	<input type="checkbox"/>	_____
Voltmeter	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fuel Level Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Engine Oil Pressure Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Exhaust Pyrometer Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Engine Coolant Temperature Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____

Transmission Oil Temperature Gauge	<input type="checkbox"/>	<input type="checkbox"/>	_____
Low Air Pressure Indicator (Light and Buzzer)	<input type="checkbox"/>	<input type="checkbox"/>	_____
Speedometer/Trip Odometer, Electronic	<input type="checkbox"/>	<input type="checkbox"/>	_____
Tachometer with Hourmeter, Electronic	<input type="checkbox"/>	<input type="checkbox"/>	_____
High Beam Indicator	<input type="checkbox"/>	<input type="checkbox"/>	_____
Parking Brake On Indicator	<input type="checkbox"/>	<input type="checkbox"/>	_____
Key Type Starting	<input type="checkbox"/>	<input type="checkbox"/>	_____
Engine Shutoff – Key-Type Control	<input type="checkbox"/>	<input type="checkbox"/>	_____
Courtesy Light Switch (Head and Clearance)	<input type="checkbox"/>	<input type="checkbox"/>	_____
Directional Signal	<input type="checkbox"/>	<input type="checkbox"/>	_____
Premium Interior with Cloth/Vinyl Seats	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fire Extinguisher – 5lb. ABC/AMEREX	<input type="checkbox"/>	<input type="checkbox"/>	_____

Cab (Exterior Features)

Welded Steel Shell, Galvanized	<input type="checkbox"/>	<input type="checkbox"/>	_____
Rust Preventative Procedures	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fender Extensions	<input type="checkbox"/>	<input type="checkbox"/>	_____
Vents – Screened, Fresh Air Inlet for Heater	<input type="checkbox"/>	<input type="checkbox"/>	_____
Cab Steps – Two Step Aluminum with	<input type="checkbox"/>	<input type="checkbox"/>	_____

Self Cleaning Threads,

and bright finish straps

Bright finish Air intake grille	<input type="checkbox"/>	<input type="checkbox"/>	_____
Safety Glass Windows	<input type="checkbox"/>	<input type="checkbox"/>	_____
Exterior Sun Visor	<input type="checkbox"/>	<input type="checkbox"/>	_____
Bright Finish Grill and Surround	<input type="checkbox"/>	<input type="checkbox"/>	_____
Tinted Two piece Windshields, Side and Rear Glass	<input type="checkbox"/>	<input type="checkbox"/>	_____
Windshield Wipers – Two, Fixed Arm and Blade Type	<input type="checkbox"/>	<input type="checkbox"/>	_____
Wiper Motor – Electric (2), Two speed Intermittent	<input type="checkbox"/>	<input type="checkbox"/>	_____
Windshield Washers – Electric Wiper Mtd. with 5 qt. (4.7 L) Translucent Reservoir	<input type="checkbox"/>	<input type="checkbox"/>	_____
Mirrors – West Coast Bright Finish, Includes 8” Convex RH & LH with Stainless Swing Away Arms	<input type="checkbox"/>	<input type="checkbox"/>	_____
Headlamps – 2 Flush Mounted with Replaceable Bulb	<input type="checkbox"/>	<input type="checkbox"/>	_____
Daytime Running Lights	<input type="checkbox"/>	<input type="checkbox"/>	_____
Identification and Clearance Lamps Bullet (5)	<input type="checkbox"/>	<input type="checkbox"/>	_____
Side Markers - Lamps and Reflectors	<input type="checkbox"/>	<input type="checkbox"/>	_____
Front Turn Signals	<input type="checkbox"/>	<input type="checkbox"/>	_____
Transistorized Flasher	<input type="checkbox"/>	<input type="checkbox"/>	_____
Horns – Air, 2 Mounted each side of Cab & Electric (Single Tone)	<input type="checkbox"/>	<input type="checkbox"/>	_____

Doors – Galvanized Steel with: ☐ ☐ _____

Power Windows (Tinted) and locks &
Visibility Door

Grab Handles – Aluminum RH & LH Behind Door ☐ ☐ _____

Cab Mounting – Dual Air Suspended Rear ☐ ☐ _____

Fuel Tank

Fuel Tank – LH 111 Gallon Aluminum ☐ ☐ _____

DEF Tank – 6.6 Gallon Left Sid Frame Mounted ☐ ☐ _____

Air Brakes

Air Dryer Heated 1200 w/ coalescing Oil Filter ☐ ☐ _____

Aluminum Air Tanks ☐ ☐ _____

ABS System ☐ ☐ _____

Hand Control Valve for Service Brakes ☐ ☐ _____

Manual Drain Valves w/ lanyards on All Tanks ☐ ☐ _____

Increased Air Capacity ☐ ☐ _____

Trailer Air Brake Connection to end of frame ☐ ☐ _____

Trailer Electrical Receptical, end of frame ☐ ☐ _____

Electrical

Electric Circuit Protection Package ☐ ☐ _____

Waterproof Electrical Connections ☐ ☐ _____

Paint

Paint Cab & Interior – DuPont White ☐ ☐ _____

Chassis & Running Gear – DuPont Black ☐ ☐ _____

Made in the USA

Engine's Final Assembly in United States ☐ ☐ _____

Chassis Final Assembly in United States ☐ ☐ _____

Service Location

Factory Authorized Parts Service and Warranty Service ☐ ☐ _____

Facility staffed with Full Time Factory Trained

Personnel to be located within ____75____ miles
of domiciled location.

Warranty

1 year / 100,000 mile Base Warranty on Chassis ☐ ☐ _____

3 year / 250,000 mile Parts & Labor Warranty on engine ☐ ☐ _____

“From Fan Hub to Fly-wheel” **Specifically Including:**

Air Compressor ☐ ☐ _____

EGR Control Valve	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fuel Injectors	<input type="checkbox"/>	<input type="checkbox"/>	_____
Exhaust After Treatment System	<input type="checkbox"/>	<input type="checkbox"/>	_____
Fuel Supply Pump	<input type="checkbox"/>	<input type="checkbox"/>	_____
Starter	<input type="checkbox"/>	<input type="checkbox"/>	_____
Turbocharger	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 year / 500,000 mile Warranty – 100% Parts & Service on Major Engine Components	<input type="checkbox"/>	<input type="checkbox"/>	_____
3 year / 300,000 mile Warranty – 100% Parts & Labor on Transmission, , and Frame	<input type="checkbox"/>	<input type="checkbox"/>	_____
Roadside Assistance & Engine Towing – 2 Year / 250,000 on Engine	<input type="checkbox"/>	<input type="checkbox"/>	_____
5 year / 500,000 miles on Axles	<input type="checkbox"/>	<input type="checkbox"/>	_____
3 year / 300,000 mile Warranty on PTO	<input type="checkbox"/>	<input type="checkbox"/>	_____

Dump Body Specs

Installed 56" Side Height / 62" Tailgate Height
8" X 2" X 1/4" Tubing Main Frame
6" X 4" Formed Channel Crossmembers on 12" Centers
1/4" AR450 Steel, Front, Sides & Floor 3/16"
AR450 Hi Lift Combo Tailgate
1/4" X 4" X 6" Tubing Top Rail
Sloped Front /
Straight Rear Aero Cab Pro Mounted Electric Tarp System Installed (Mesh)
Ladder w/ Platform & 2 Inside Steps Mounted on Drivers Side Front
6 3/4" Heavy Duty Pipe Apron Sand Style Tailgate
(Outer Frame Only no Center Ribs) Inverted Angle Mounted on Top of Rail & Gate to Shed
Debris (No Boards)
1 Pair of Oval LED S/T/T Lights Mounted in Rear Rib
1 Additional Pair of Marker Lights Installed at Front / Bottom Fender
1 Pair of Marker Lights Installed on Front of Cab Protector
Oil Site Glass Installed on Hydraulic Tank Drivers Side
Customer Supplied Pump & PTO (M-Drive) Install Tipper Valve
Front Metal Gravel Guards at Front of Body
1 Pair of Oval LED Strobes Installed on Front of Cab Protector
1 Pair of Oval LED Strobes Installed in Rear
Rib 79.5" Tall Full Width
24" Cab Protector Installed Black in Color Install
50 Ton Pintle Hitch / Gladhands on Hoses / 6- & 7-Way Receptacles Install Hitch at 25" Height /
Tie into Dealer Supplied Air & Electric
Install Chassis Provided S/T/T Lights with Integrated Back Up Lights Install 3 Light Cluster in
Rear Hinge /
Install Brake Controller